

# MISTRAL

## Technical details

Manufacturing method	Tufted
Pile type	Looppile
Special treatment Kleenaway	Yes
Dyeing method	Space dye
Pile content	100 % PA Space dyed
Gauge	1/10
Backing	Action Backing
Pile weight	ca. 900 gr/m <sup>2</sup>
Pile height	ca. 4,0 mm
Total Thickness	ca. 6,0 mm
Total weight	ca. 1980 gr/m <sup>2</sup>
Tuft density	ca. 205000 /m <sup>2</sup>
Width	4 m
Flammability classification	Cfl S1 according to EN13501-1
Electrostatic properties	Walking Test ≤ 2,0 KV Resistance ≥ 10 <sup>10</sup>
Suitability	EN1307 - 32 - Commercial general
Sound absorption	24 dB acc. to ISO 10140-1
Colour fastness :	
To light	≥ 5 according to ISO 105B02
To rubbing	≥ 3 according to ISO 105-X12

## Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.

This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.

All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

## Pile reversal / shading

Carpets may be subject to permanent pile reversal, also known as "shading" or "water-marking".

The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.

We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.

48830

48820

48840

48849



16

EN 1307

Manufactured by: TAPIBEL nv.  
Industrielaan 4 - B-3900 Overpelt  
DOP 000488A-002 - EN 14041

MISTRAL (TU0007)

For use as floor covering in buildings  
(EN 14041) according to the manufacturer's specifications