

Colour Index, All colourways (Colour Index), MPC1950



Due to variations in PC monitors the colour displayed may vary from actual product. Please order a free sample for exact colour match.

Product Detail

Width	130 cm
Width	130 cm
Weight	440 gsm
Weight	440 gsm
Fire rating	Euro Class B
Fire rating	Euro Class B
LRV Value	56
LRV Value	56
VOC Rating	A+
VOC Rating	A+
VOC Certificate	W11/09/07
VOC Certificate	W11/09/07
Cleanability	EN235 Extra Scrubbable
IMO Rated	BV0062
Cleanability	EN235 Extra Scrubbable
IMO Rated	BV0062
Lightfastness	Excellent. (7 out of 8 to BSEN20105)
Lightfastness	Excellent. (7 out of 8 to BSEN20105)
Recommended Adhesive	Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed surfaces use Murabond Sealed Surface Adhesive. For other surfaces contact Customer Services on 08705 117 118.
Recommended Adhesive	Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed surfaces use Murabond Sealed Surface Adhesive. For other surfaces contact Customer Services on 08705 117 118.
Pattern Repeat	0
Pattern Repeat	0
Pattern Offset	0
Pattern Offset	0
Pattern Overlap	5
Pattern Overlap	5
Hanging Type	By Reverse Hanging
Hanging Type	By Reverse Hanging

If you require further information about any Muraspec product or service please contact our Customer Service Team
United Kingdom +44 (0)8705 117 118
UK Export +44 (0)1442 270555
United Arab Emirates +971 4 338 7399
France +33 1 41 32 29 00
Poland +48 22 648 4467