



- COMMERCIAL / RECREATIONAL
 - 500 series
 - 600 series
 - 700 series
 - 800 series
 - BFC series
 - Natural series
 - Reco series
 - REPTiles
 - Stikibak
- FITNESS
- POOL
- SPORTS
- EQUINE
- PLAY
- SAFETY
- INDUSTRIAL
- BALLISTIC
- REFERENCE GALLERY


- EMAIL US
- WE'LL CALL YOU
- DOWNLOAD A CATALOG
- CONTACT US
- REFERENCE GALLERY

NEOFLEX™ 600 SERIES

Commercial / Recreational Flooring

Performance can take many forms. The most beautiful is presented here.

A designer's dream - Neoflex™ 600 Series is a high-density sheet floor that is evocative of terrazzo style flooring, while also being sound insulating, flexible and durable. Neoflex™ 600 Series is made entirely of Mixed Colored EPDM Rubber, and is thus suitable for all interior applications - be it offices, healthcare facilities, schools, retail, stadia, concert halls, cinemas, libraries, washrooms, pool surrounds, fitness gyms, walkways, or exhibitions.



- Description
- Specifications
- Colors
- ThinkColor
- Downloads
- Online Brochure

SPECIFICATIONS - NEOFLEX™ 600 SERIES

Thickness	3 - 12 mm [1/8 in. - 1/2 in.]	
Roll Length	10 -25 m [50 ft.]	
Roll Width	1.2 m [4 ft.]	
Interlock Size	575 mm x 595 mm [22 2/3 in. x 23 7/16 in.]	
Square Tile Size	608 mm x 608 mm [24 in. x 24 in.]	
Density	± 1,300 kg/m3 [81.04 lbs./cu. Ft.]	
Resilience	40%	DIN 18032
Tensile Strength	0.91 N/mm2	DIN 18032
Tear Strength	9.7 N/mm	ASTM D624
Taber Abrasion	0.66 gr	ASTM C504
Shore Hardness A	60	ASM D2240
Remaining Indentation	0.05 mm	DIN 53960
Noise Absorption	13dB [4 mm]	EN 20140/ISO 140
Flammability	Class 1 [Sport Use]	ASTM D2859
Flammability	Cfl-s1 [Commercial Use]	EN 13501
Flammability	Class 1 [Commercial Use]	ASTM E648
Coefficient of Friction	Dry 1.1, Wet 1.03	ASTM D2047-97
Slip Resistance	R10	ANZS 4596:1999
Thermal Stability	-40°C - 100°C	ASTM C1026

Neoflex Rubber Flooring is made of direction free rubber chips supplied in a variety of sizes and colors. Variations in shading and dispersion is normal.

