



NEOFLEX™ 800 SERIES

Commercial / Recreational Flooring

Your supreme floor awaits.

Available in 20 solid EPDM colors, Neoflex™ 800 Series is ideally suited as a monolithic flooring statement. It is also very popular for borders, highlights and logos in conjunction with our other floors.



Description

Specifications

Colors

ThinkColor

Downloads

Online Brochure

SPECIFICATIONS - NEOFLEX™ 800 SERIES

Thickness	3 - 12 mm [1/8 in. - 1/2 in.]	
Roll Length	10 -25 m [50 ft.]	
Roll Width	1.2 m [4 ft.]	
Square Tile Size	608 mm x 608 mm [24 in. x 24 in.]	
Interlock Size	575 mm x 595 mm [22 2/3 in. x 23 7/16 in.]	
Density	± 1,300 kg/m3 [81.04 lbs./cu. Ft.]	
Resilience	40%	DIN 18032
Tensile Strength	0.91 N/mm2	DIN 18032
Tear Strength	9.7 N/mm	ASTM D624
Taber Abrasion	0.66 gr	ASTM C504
Shore Hardness A	60	ASM D2240
Remaining Indentation	0.05 mm	DIN 53960
Noise Absorption	13dB [4 mm]	EN 20140/ISO 140
Flammability	Class 1 [Sport Use]	ASTM D2859
Flammability	Class 1 [Commercial Use]	ASTM E648
Flammability	Bfl-s1 [Commercial Use]	EN 13501
Coefficient of Friction	Dry 1.1, Wet 1.03	ASTM D2047-97
Slip Resistance	R10	ANZS 4596:1999
Thermal Stability	-40°C - 100°C	ASTM C1026
Neoflex Rubber Flooring is made of direction free		
rubber chips supplied in a variety of sizes and		
colors. Variations in shading and dispersion is		
normal.		



COMMERCIAL / RECREATIONAL

- ☐ 500 series
- ☐ 600 series
- ☐ 700 series
- ☒ 800 series
- ☐ BFC series
- ☐ Natural series
- ☐ Reco series
- ☐ REPTiles
- ☐ Stikibak

- ☐ FITNESS
- ☐ POOL
- ☐ SPORTS
- ☐ EQUINE
- ☐ PLAY
- ☐ SAFETY
- ☐ INDUSTRIAL
- ☐ BALLISTIC

REFERENCE GALLERY

EMAIL US

WE'LL CALL YOU

DOWNLOAD A CATALOG

CONTACT US

REFERENCE GALLERY

