

NEW MELODY

Technical details

Manufacturing method	Tufted
Pile type	Looppile Graphics
Anti soil treatment	Yes
Dyeing method	Solution dyed
Pile content	90 % Polypropylene - 10% Polyamide
Gauge	1/10
Backing	Action Backing / Gel Backing
Pile weight	ca 450 gr/m ²
Pile height	ca 4,0 mm
Total thickness	ca 6,0 mm
Total weight : AB	ca 1450 gr/m ²
Total weight : Gel	ca 1570 gr/m ²
Tuft density	ca. 160 000 /m ²
Width	4m
Flammability classification	BS 4790 Low Radius of Effects of Ignition
Electrostatic properties	IBM/ICL < 4.55 x 10 ¹¹ at 40% RH at 20°C
Suitability	Domestic General - according to EN 1307 Heavy Domestic/General Contract - acc. to BS 7131
Sound absorption	24dB ISO 140-8
Colour fastness :	To light > 6 according to ISO 105-B02 To rubbing > 3-4 according to ISO 105-X12

Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.

This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.

All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

Pile reversal / shading

Carpets may be subject to permanent pile reversal, also known as "shading" or "water-marking".

The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.

We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.

37450

37460

37421

37470

37489



13

EN 1307

Manufactured by: TAPIBEL nv.
Industrielaan 4 - B-3900 Overpelt
DOP 000374B - EN 14041

NEW MELODY

For use as floor covering in buildings
(EN 14041) according to the manufacturer's
specifications

TÜV Emission testing - The results comply with the emission threshold of:

AgBB - Germany

French VOC regulation

Belgian VOC regulation

LEED V4 (outside North America)

BREEAM Exemplary level

www.tapibel.be - sales@tapibel.be

Tel : +32 11 80 48 50 - Fax: +32 11 64 75 46 Industrielaan 4 - Nolimpark 1319 B-3900 Overpelt - Belgium

Tapibel