

TECHNICAL DATA SHEET



SSG,SSG Tedlar P1479,P1479



Due to variations in PC monitors the colour displayed may vary from actual product. Please order a free sample for exact colour match.

Product Detail

Width	130 cm
Width	130 cm
Weight	547 gsm
Weight	547 gsm
Fire rating	Euro Class B
Fire rating	Euro Class B
LRV Value	84
LRV Value	84
VOC Rating	A+
VOC Rating	A+
VOC Certificate	W11/09/07
VOC Certificate	W11/09/07
Cleanability	EN235 Extra Scrubbable
IMO Rated	BV0062
Cleanability	EN235 Extra Scrubbable
IMO Rated	BV0062
Lightfastness	Excellent. (7 out of 8 to BSEN20105)
Lightfastness	Excellent. (7 out of 8 to BSEN20105)
Biocide	Yes
Biocide	Yes
Recommended Adhesive	Murabond Super Heavy on an absorbent surface & FXB Contact adhesive for external angles. For other surfaces contact customer services on 08705 117 118.
Recommended Adhesive	Murabond Super Heavy on an absorbent surface & FXB Contact adhesive for external angles. For other surfaces contact customer services on 08705 117 118.
Pattern Repeat	0
Pattern Repeat	0
Pattern Offset	0
Pattern Offset	0
Pattern Overlap	6
Pattern Overlap	6

Stain Resistant

Yes

Hanging Type

By Reverse Hanging

Stain Resistant

Yes

Hanging Type

By Reverse Hanging

If you require further information about any Muraspec product or service please contact our Customer Service Team

United Kingdom +44 (0)8705 117 118

UK Export +44 (0)1442 270555

United Arab Emirates +971 4 338 7399

France +33 1 41 32 29 00

Poland +48 22 648 4467