## **TECHNICAL DATA SHEET**



## Studio Suite, Thai, P1540



Due to variations in PC monitors the colour displayed may vary from actual product. Please order a free sample for exact colour match.

| Product Detail       |   |
|----------------------|---|
| Width                | 130 cm  |
| Width                | 130 cm  |
| Weight               | 410 gsm   |
| Weight               | 410 gsm   |
| Fire rating          | Euro Class B  |
| Fire rating          | Euro Class B  |
| LRV Value            | 66  |
| LRV Value            | 66  |
| VOC Rating           | A+  |
| VOC Rating           | A+  |
| VOC Certificate      | W11/09/08   |
| VOC Certificate      | W11/09/08   |
| Cleanability         | EN235 Extra Scrubbable  |
| IMO Rated            | BV0062  |
| Cleanability         | EN235 Extra Scrubbable  |
| IMO Rated            | BV0062  |
| Lightfastness        | Excellent. (7 out of 8 to BSEN20105)  |
| Lightfastness        | Excellent. (7 out of 8 to BSEN20105)  |
| Biocide              | Yes   |
| Biocide              | Yes   |
| Recommended Adhesive | Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed<br>surfaces use Murabond Sealed Surface Adhesive. For other surfaces<br>contact Customer Services on 08705 117 118.<br>Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed<br>surfaces use Murabond Sealed Surface Adhesive. For other surfaces |
| Pattern Repeat       | contact Customer Services on 08705 117 118.<br>0  |
| Pattern Repeat       | 0   |
| Pattern Offset       | 0   |
| Pattern Offset       | 0   |
| Pattern Overlap      | 6   |
| Pattern Overlap      | 6   |
|                      |   |

Hanging Type

Hanging Type

By Reverse Hanging

## By Reverse Hanging

If you require further information about any Muraspec product or service please contact our Customer Service Team United Kingdom +44 (0)8705 117 118 UK Export +44 (0)1442 270555 United Arab Emirates +971 4 338 7399 France +33 1 41 32 29 00 Poland +48 22 648 4467