TECHNICAL DATA SHEET



Muralon, Corduroy, P1958



Due to variations in PC monitors the colour displayed may vary from actual product. Please order a free sample for exact colour match.

Product Detail

Pattern Overlap

Width 130 cm
Width 130 cm
Weight 360 gsm
Weight 360 gsm
Fire rating Euro Class B
Fire rating Euro Class B

 LRV Value
 73

 LRV Value
 73

 VOC Rating
 A+

 VOC Rating
 A+

 VOC Certificate
 W11/09/07

 VOC Certificate
 W11/09/07

 IMO Rated
 BV0062

Cleanability EN235 Extra Scrubbable

IMO Rated BV0062

Cleanability EN235 Extra Scrubbable

Lightfastness Excellent. (7 out of 8 to BSEN20105)

Lightfastness Excellent. (7 out of 8 to BSEN20105)

Biocide Yes
Biocide Yes

Recommended Adhesive Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed

surfaces use Murabond Sealed Surface Adhesive. For other surfaces

contact Customer Services on 08705 117 118.

Recommended Adhesive Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed surfaces use Murabond Sealed Surface Adhesive. For other surfaces

5

contact Customer Services on 08705 117 118.

 Pattern Repeat
 0

 Pattern Repeat
 0

 Pattern Offset
 0

 Pattern Offset
 0

 Pattern Overlap
 5

Hanging Type

By Reverse Hanging

Hanging Type

By Reverse Hanging

If you require further information about any Muraspec product or service please contact our Customer Service Team United Kingdom +44 (0)8705 117 118
UK Export +44 (0)1442 270555
United Arab Emirates +971 4 338 7399
France +33 1 41 32 29 00
Poland +48 22 648 4467