













Technical information Create








Construction: Woven vinyl flooring, product standard EN 15114

www.bolon.com for updated information




Included in EN 15114

	Use classification		EN 685	33 Heavy commercial
	Weight	Rolls Tiles	ISO 8543	2,9 kg/m ² 3,9 kg/m ²
	Thickness	Rolls Tiles	ISO 1765	2,5 mm 3,0 mm
	Roll dimension	Width Length	EN 426	2000 mm 25 m
	Tile dimension		EN 994	500 x 500 mm. 20 pcs/box, 5 sqm
	Castor Chair		EN 985	Continous use
	Body Voltage		EN 1815**	Fulfilled
	Thermal resistance		ISO 8302	Suitable for underfloor heating
	Impact sound insulation*		EN ISO 10140	11 dB
	Airborne sound absorption*		EN ISO 354	0,05
	Colour fastness to light*		EN ISO 105-B02	8
	Dimension stability	Rolls Tiles	ISO 2551 EN 986	Fulfilled Fulfilled

Additional tests

	Anti slip property		DIN 51130	R9
	Friction		EN 13893	> 0,3
	Pendulum		EN 13036-4	94-95
	Reaction to fire		EN 13501-1	B _{fl} -s1
	Critical radiant flux		ASTM E 648	Class 1
	Smoke density		ASTM E 662	< 450
	Emission		EN ISO 16000-10	<50 µg/m ² h

Certifications

	CE certificate		EN 14041	No 0402-CPD-419005
	Floor Score certificate	Rolls Tiles	SCSEC-10.2-2007	SCS-FS-02007 SCS-FS-02240
	Classification	Rolls Tiles	CSTB	Under testing at time of printing Under testing at time of printing

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.

