


















TECSOM PRIMA

Factory ISO 9001 Quality Management System
Factory ISO 14 001 Environmental Management System
Factory OHSAS 18001 Health, Safety and Security Management System

SPECIFICATIONS					Article n° : 112380505-00XXX	
DESCRIPTION	NORM	DATA		12 colors	Reflectance Index (%)	
Composition fibreuse / Pile Fibre		100% Polyamide (Solution dyed)		(000) / 017	5,0%	
Jauge / Gauge		1/10 loop pile		(001) / 034	8,9%	
Serrage / Number of Stitches	ISO 1763	35/dm		(002) / 032	17,5%	
Densité / Tuft Density	ISO 1763	143 500 Stitches/m ²		(003) / 028	3,9%	
Poids de fil / Total pile mass	ISO 8543	510 g/m ²		(004) / 026	5,1%	
Masse de velours utile / Mass of pile above the substrate	ISO 8543	300 g/m ²		(005) / 024	9,0%	
Epaisseur velours utile / Thickness of pile above the substrate	ISO 1766	3.0 mm		(006) / 045	5,3%	
Densité du velours de surface / Surface pile density	ISO 8543	0,100 g/cm ³		(007) / 044	8,7%	
Masse totale / Total Weight	ISO 8543	4280 g/m ²		(008) / 064	15,1%	
Epaisseur totale / Total Thickness	ISO 1765	6.8 mm		(009) / 097	6,5%	
Premier dossier / Primary Backing		Non tissé / Non woven primary backing		(010) / 100	18,5%	
Envers / Backing		Backing System Matières recyclées renforcées par un voile de verre 100 % recycled vinyl backing reinforced with glass fiber		(011) / 087	9,0%	
Dimensions / Tile Size		50x50cm				
Dalles par boîte / Tiles per Box		20 = 5m ²				
Sens de pose / Installation						
Base d'impression / Printing facilities		NO				
TECHNICAL PERFORMANCES						
Classification (EN 1307)	Class: 23/32 - Commercial General LC1					
Classement UPEC (Référentiel NF 262)	Classement: U3P3E1C0 Certificat n°: 349T-008.1					
 Fire rating	EN 13501-1		 Impact noise reduction	ISO 717/2	ΔL _(w) 24 dB	
	BflS1		 Sound absorption	ISO 11654	α _w = 0,15 (H)	
 Electrostatic properties	ISO 6356	≤ 2,0kV	 Colour Fastness	EN 105 - B02	7/8	
			 Castor Chair	EN 985	Passed R _{≥2,4}	
	ISO 10965	RT ≈ 10 ¹⁰ Ω	 Heated Floor	ISO 10456	0,09 m ² K/W	
 Dimensional Stability	EN 986			CE N° 0679-CPR-0196 07 EN 14041: 2004 EN1307		
	≤ 0,10%					
ENVIRONMENTAL ISSUES						
 ÉMISSIONS DANS L'AIR INTÉRIEUR		 A+ A B C		LEED: This product contributes to obtain points towards MR2, MR4, MR5, IEQ4.1 and IEQ4.3 credits to the LEED certification of your buildings.		
HQE : Ce produit participe à 9 des cibles nécessaires à l'obtention de la certification HQE d'un bâtiment. Se reporter à la FDES suivant NF P01-010 pour l'ACV.						
Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.						
Updated on 16/12/2014						