

Epoca Profile Broadloom

Product Description



Product description	Methods	Product data	
Construction characteristics			
Structure	ISO 2424	Woven loop pile	
Pile material	DIR 96/73, 96/74	100% polyamide	
Coloration	-	Continuous dyed	
Backing	eTL	WT - Woven textile	
Total thickness	ISO 1765	Apr 3,5 mm.	
Total carpet weight	ISO 8543	Apr 2.350 g/m2	
Pile yarn weight	eTL	625 g/m2	
	.	18.44 oz./yd2	
Soil protection	eTL	Yes	
Performance characteristics			
Guarantee	eTL	Contract certificate	
Static control	eTL	Permanently antistatic	
Acou.insu. from impact noise	eTL	15 dB	
Acoustical absorption	eTL	0,15 aW	
Suitability underfloorheating	eTL	Apr 0,06 m2K/W	
Light reflectance	eTL	Testreport	
Safety & Environment			
Fire classification	MK GODKENDELSE	Approved	
	DIBT AbZ.no.	Z-156.601-377	
	VKF/AEAI	Approved	
	EN 13501-1 Euroclass	Cfl-s1	
	CE Labeling	EN 14041	Certified
		CPR	1021-CPR-006-2/16
		Declaration of Performance	DOP 1C-PA-WT
		Notified body no.	1021
		Ce Year	08
		Content of PCP EN 12673	DL
Indoor climate	Formaldehyde emission	NA	
	Slip resistance EN 13893	Class DS	
	DIM certificate	No. 006	
	Green Label Plus	Approved	
	GECA	Approved	
	Guides		
	Installation + adhesive guide	DK	Dansk
		N	Norsk
S		Svensk	
GB		English	
D		Deutsch	
F		Francais	
Cleaning, stain removal	DK	Dansk	
	N	Norsk	
	S	Svensk	
	GB	English	
	D	Deutsch	
	F	Francais	

Product description	Methods	Product data
Manufacturer characteristics		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified