


# Epoca Rustic Ecotrust

## Product Description



**ege**

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
<b>Construction characteristics</b>		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96cm/Figura
Dimensional stability	EN 986	<0,2%
Total thickness	ISO 1765	Apr 5,0 mm.
Total carpet weight	ISO 8543	Apr 2.400 g/m2
Pile yarn weight	eTL	450 g/m2
Soil protection	eTL	Yes

### Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	16 dB
Acoustical absorption	eTL	0,20 aW
Suitability underfloorheating	eTL	Apr 0,09 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fastness to ozone	AATCC 129	4.0
Colour fast.Oxides of nitrogen	AATCC 164	4.0
Other performance tests	ASTM D5252 Hexapod	4.5
	AATCC 134 Electrostatic propensity	1.1 kV

### Safety & Environment

Fire classification	MK GODKENDELSE	Approved
	VKF/AEAI	Approved
	ASTM E-648	Class 1
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	ASTM E 662	Approved
	CE Labeling	EN 14041
	CPR	1021-CPR-010-1/16
	Declaration of Performance	DOP 5B-PA-ECT350
	Notified body no.	1021
	Ce Year	17

Product description	Methods	Product data
Indoor climate	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
	DIM certificate	No. 006
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
Environment	Cradle To Cradle Certified	Ecotrust, Bronze certified

### Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Installation tiles	Direction of installation	Quarter turn/ monolithic
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified