

### **PHYSICAL CONSTRUCTION:**

CONSTRUCTION:	Textured Patterned Loop (Non-Ortho Phthalate Construction)
FACE FIBER:	ECONYL (100% regenerated Type 6 Nylon)
DYE METHOD:	Solution
GAUGE:	5/64
STITCHES PER INCH:	9.33
PILE THICKNESS:	.095 inches
TUFTED YARN WEIGHT:	14 Ounces Per Square Yard
DENSITY:	Average Density = 5,305; Weight Density = 74,273
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Infinity Modular Reinforced Composite Closed Cell Polymer
STANDARD SIZE:	18" X 36" Modular Tiles
INSTALLATION METHOD:	Horizontal Brick Ashlar

### **ENVIRONMENTAL:**

MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
CRI GREEN LABEL PLUS ID:	GLP7616

### **WARRANTIES:**

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

### **PRODUCT TESTING:**

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
DIMENSIONAL STABILITY AACHEN TEST:	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

### **RECOMMENDED ADHESIVE:**

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.