

# Shadow Play

<b>Construction</b>	Tufted, Textured Loop
<b>Face Fiber</b>	WearOn® Nylon
<b>Dye Method</b>	Millitron®
<b>Soil and Stain Protection</b>	MilliGuard®
<b>Antimicrobial</b>	AlphaSan® Built-In Protection
<b>Gauge</b>	1/10
<b>Rows</b>	14.4/in.
<b>Tuft Density</b>	144.0/sq.in.
<b>Density Factor</b>	496,730
<b>Secondary Backing</b>	PVC-Free Underscore™ ES cushion
<b>Tile Size</b>	50cm x 50cm (19.7 x 19.7 in.)
<b>Nominal Total Weight</b>	89.0 oz./sq.yd. (3,017.8 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450
<b>Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)</b>	Self-Extinguishing
<b>Lightfastness (AATCC 16E)</b>	≥ 4.0 at 80 hrs.
<b>Crocking (AATCC 165)</b>	≥ 4.0 wet or dry
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV, Permanent Conductive Fiber
<b>Dimensional Stability - Aachener Test (DIN Std 54318)</b>	≤ 0.2%
<b>Texture Appearance Retention Rating (TARR)</b>	Severe Traffic End-Use Applications
<b>Recommended Maintenance</b>	Capture® Carpet and Fabric Care
<b>Indoor Air Quality - CRI Green Label Plus™</b>	GLP0793, Carpet Category 5Y

Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



## Warranties:

Lifetime Antimicrobial Protection (AlphaSan®)	Lifetime Face Fiber Wear
Lifetime Antistatic	Lifetime Floor Compatibility
Lifetime Color Pattern Permanency	Lifetime Floor Release
Lifetime Cushion Resiliency	Lifetime Moisture Resistance
Lifetime Delamination of Backing	Lifetime Staining/Soiling
Lifetime Dimensional Stability	Lifetime Tuft Bind
Lifetime Edge Ravel	Flammability