



PRODUCT SPECIFICATIONS DOMO Slide DS 40 M

Applications	Soccer	
Fibre	Polyethylene / UV-stabilized / Straight / 100% Monofilament 12.000 dtex / 6 Monofilaments / ca. 300 μm thickness	
Production Method	Linear tufting	
Gauge	5/8"	
# stitches / m	145 / m	$\pm 10\%$
# tufts / m^2	9.135 / m^2	$\pm 10\%$
# piles / m^2	109.620 / m^2	$\pm 10\%$
Pile Height	40 mm	$\pm 5\%$
Pile Weight	1.050 gr / m^2	$\pm 10\%$
Total Height	42 mm	$\pm 5\%$
Total Weight	2.302 gr / m^2	$\pm 10\%$
Tuft Cloth	Polypropylene, UV-stabilized, 252 gr / m^2	$\pm 5\%$
Backing	Latex, 1.000 gr / m^2	$\pm 10\%$
Infill	Sand (ca. 15 kg / m^2 , System & material related) (> 80% roundness) Rubber (ca. 5 kg / m^2 , System & material related)	
Roll Width	400 cm	
Roll Length	As per lay-out	
Colour	Green	
Colour Lines	White / Yellow	
Colour Fastness	Scale 7 (DIN 54004)	
UV-Stability	> 3.000 hours UV-A	
Water Permeability	$6 \cdot 10^{-4}$ m/s	
Pile Anchorage	> 30 N	

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE

DOMO® SPORTS GRASS IS A BRAND OF SPORTS & LEISURE GROUP NV

Industriepark-West 43 | B - 9100 Sint-Niklaas F | +32 (0)3 780 45 73 | T +32 (0)3 780 45 75 | domosportgrass.com



PRODUCT SPECIFICATIONS DOMO Slide DS 45 M

Applications	Soccer	
Fibre	Polyethylene / UV-stabilized / Straight / 100% Monofilament 12.000 dtex / 6 Monofilaments / ca. 300 μ m thickness	
Production Method	Linear tufting	
Gauge	5/8"	
# stitches / m	145 / m	$\pm 10\%$
# tufts / m ²	9.135 / m ²	$\pm 10\%$
# piles / m ²	109.620 / m ²	$\pm 10\%$
Pile Height	45 mm	$\pm 5\%$
Pile Weight	1.150 gr / m ²	$\pm 10\%$
Total Height	47 mm	$\pm 5\%$
Total Weight	2.402 gr / m ²	$\pm 10\%$
Tuft Cloth	Polypropylene, UV-stabilized, 252 gr / m ²	$\pm 5\%$
Backing	Latex, 1.000 gr / m ²	$\pm 10\%$
Infill	System & material related (See laboratory test reports)	
Shock pad	System & material related (See laboratory test reports)	
Roll Width	400 cm	
Roll Length	As per lay-out	
Colour	Green	
Colour Lines	White / Yellow	
Colour Fastness	Scale 7 (DIN 54004)	
UV-Stability	> 3.000 hours UV-A	
Water Permeability	6.10 ⁻⁴ m/s	
Pile Anchorage	> 30 N	

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE



PRODUCT SPECIFICATIONS DOMO Slide DS 50 M

Applications	Soccer
Fibre	Polyethylene / UV-stabilized / Straight / 100% Monofilament 12.000 dtex / 6 Monofilaments / ca. 300 µm thickness
Production Method	Linear tufting
Gauge	5/8"
# stitches / m	145 / m $\pm 10\%$
# tufts / m ²	9.135 / m ² $\pm 10\%$
# piles / m ²	109.620 / m ² $\pm 10\%$
Pile Height	50 mm $\pm 5\%$
Pile Weight	1.250 gr / m ² $\pm 10\%$
Total Height	52 mm $\pm 5\%$
Total Weight	2.502 gr / m ² $\pm 10\%$
Tuft Cloth	Polypropylene, UV-stabilized, 252 gr / m ² $\pm 5\%$
Backing	Latex, 1.000 gr / m ² $\pm 10\%$
Infill	See laboratory test report
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Lines	White / Yellow
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 3.000 hours UV-A
Water Permeability	6.10 ⁻⁴ m/s
Pile Anchorage	> 30 N

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE

DOMO® SPORTS GRASS IS A BRAND OF SPORTS & LEISURE GROUP NV

Industriepark-West 43 | B - 9100 Sint-Niklaas F | +32 (0)3 780 45 73 | T +32 (0)3 780 45 75 | domosportgrass.com



SPORTS GRASS

PRODUCT SPECIFICATIONS DOMO Slide DS 60 M

Applications	Soccer
Fibre	Polyethylene / UV-stabilized / Straight / 100% Monofilament 12.000 dtex / 6 Monofilaments / ca. 300 μ m thickness
Production Method	Linear tufting
Gauge	5/8"
# stitches / m	145 / m \pm 10%
# tufts / m ²	9.135 / m ² \pm 10%
# piles / m ²	109.620 / m ² \pm 10%
Pile Height	60 mm \pm 5%
Pile Weight	1.500 gr / m ² \pm 10%
Total Height	62 mm \pm 5%
Total Weight	2.752 gr / m ² \pm 10%
Tuft Cloth	Polypropylene, UV-stabilized, 252 gr / m ² \pm 5%
Backing	Latex, 1.000 gr / m ² \pm 10%
Infill	System & material related (See laboratory test reports)
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Lines	White / Yellow
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 3.000 hours UV-A
Water Permeability	6.10 ⁻⁴ m/s
Pile Anchorage	> 30 N

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE