

## Solid stripe

<b>Tuft gauge</b>	1/10 loop pile	
<b>Pilecomposition</b>	100% PA SDN	
<b>Primary Backing</b>	Non Woven	
<b>Secondary backing</b>	Bitumen	
<b>Width</b>	50 x 50 cm	± 1%
<b>Pile height</b>	3.5 mm	
<b>Pile Weight</b>	550 gr/m <sup>2</sup>	
<b>Total weight</b>	3540 gr/m <sup>2</sup>	± 15%
<b>Total Height</b>	6 mm	
<b>Number of knots</b>	181240 /m <sup>2</sup>	-7.5% .+10%
<b>Use Area</b>	Extrem / Heavy (33)	
<b>Sound Insulation</b>	Ca. 25 dB	
<b>Thermal resistance</b>	ca 0,07 M <sup>2</sup> KW	
<b>Light fastness</b>	≥ 5	
<b>Wearebility</b>	≥ 4	
<b>Water fastness</b>	≥ 4	
<b>Fire Clasification</b>	Bfl-S1 1658-CPR-3134	
<b>Abz Nr.</b>	Z-156.601-1263	
<b>Comments</b>	Noise insulation ≥ 20dB Noise absorption ca 0,15 aW	
<b>Pictures</b>	www.condorcontract.com	

## Floorsymbols



## Certificates

