

Una Tinta broadloom

Product Description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antisalissure



contract
CERTIFICATE



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted loop pile - structured
Gauge	ISO 2424	1/12
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Solution dyed
Backing	eTL	WT - Woven textile
Total thickness	ISO 1765	Apr 8,0 mm.
Surface pile thickness	ISO 1766	Apr 5,5 mm.
Tufts	ISO 1763	Apr 236.200 pr.m2
Total carpet weight	ISO 8543	Apr 2.700 g/m2
Pile yarn weight	eTL	950 g/m2
	.	28.03 oz./yd2
Surface pile density	ISO 8543.	Apr 0,135 g/cm3
Soil protection	eTL	Yes

Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	26 dB
Suitability underfloorheating	eTL	Apr 0,14 m2K/W
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	ISO 105-X12	>3
Colour fastness to rubbing dry	ISO 105-X12	>3-4
Colourfast. to water patterned	ISO 105-E01	>4

Safety & Environment

Fire classification	EN 13501-1 Euroclass	Bfl-s1
CE Labeling	EN 14041	Certified
	CPR	1020-CPR-006-1/16
	Declaration of Performance	DOP 1B-PA-WT
	Notified body no.	1021
	Ce Year	16
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk

Product description	Methods	Product data
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified