

## Traffic

<b>Tuft gauge</b>	1/10 loop pile	
<b>Pilecomposition</b>	100% PA66	
<b>Primary Backing</b>	Woven	
<b>Secondary backing</b>	AB	
<b>Width</b>	400 cm, 500 cm	± 1%
<b>Pile height</b>	4-6 mm	
<b>Pile Density</b>	0.116 gr/cm <sup>3</sup>	
<b>Pile Weight</b>	715 gr/m <sup>2</sup>	
<b>Total weight</b>	1900 gr/m <sup>2</sup>	± 15%
<b>Total Height</b>	7 mm	
<b>Number of knots</b>	177300 /m <sup>2</sup>	-7.5% .+10%
<b>Transversal resistance</b>	Hor: 3.4 x 10 12 Ver:6.5 x 10 11 Ohm	
<b>Use Area</b>	Extrem / Heavy (33)	
<b>GUT Nr.</b>	OAC2DE96 GUT	
<b>Sound Insulation</b>	Ca. 24 dB	
<b>Thermal resistance</b>	0.14 M <sup>2</sup> KW	
<b>Light fastness</b>	≥ 5	
<b>Wearebility</b>	≥ 5	
<b>Water fastness</b>	≥ 5	
<b>Fire Clasification</b>	Bfl-S1 1658-CPR-3262	
<b>Abz Nr.</b>	Z-156.601-671	
<b>Pictures</b>	www.condorcontract.com	

## Floorsymbols



## Certificates

