

# LANDMARK

## Vestige

Modular Tile

### Construction

Tufted, Textured Loop

### Tile Size

1 m x 1 m (39.4" x 39.4")

### Yarn Type

Milliken-Certified WearOn® Nylon  
Type 6,6

### Stain Repel / Stain Resist / Soil Release

StainSmart®

### Antimicrobial

AlphaSan® AF Built-In Protection†

### Dye Method

DCP (Digital Color Placement)

### Tufted Face Weight

15 oz/yd² (509 g/m²)

### Gauge

1/12

### Stitches Per Inch

9.8

### Tufts

117.6/in² (1,821/100 cm²)

### Finished Pile Height

0.13" (3.30 mm)

### Finished Pile Thickness

0.08" (2.03 mm)

### Average Density (Finished)

6,541

### Standard Backing

PVC-Free Underscore™ ES Cushion  
Available with TractionBack®

### Recycled Content by Total Weight

ES Backing: 39.3% Pre-Consumer,  
0.0% Post-Consumer  
ESP Backing: 28.6% Pre-Consumer,  
10.7% Post-Consumer

### Nominal Total Thickness

0.28" (7.1 mm)

### Nominal Total Weight

89 oz/yd² (3,024 g/m²)

### Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

### Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

### Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

### Texture Appearance Retention Rating (TARR)

Severe Traffic End-Use Applications

### Recommended Maintenance

MilliCare® Textile and Carpet Care  
Service Network

### Indoor Air Quality—CRI Green Label Plus™

GLP0793, Carpet Category 5Y

### Recommended Installation Method(s)

Monolithic

### WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®)

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.