

# THE BASICS

## The Basics Warm, Cool, Spectrum

Modular Tile

### Construction

Tufted, Textured Loop

### Tile Size

50 cm x 50 cm (19.7" x 19.7")

### Yarn Type

Milliken-Certified WearOn® Nylon and Solution-Dyed Nylon, Type 6,6

### Stain Repel / Stain Resist / Soil Release

StainSmart®

### Antimicrobial

AlphaSan® AF Built-In Protection†

### Dye Method

Continuous Dye/Solution Dye

### Tufted Face Weight

16 oz/yd<sup>2</sup> (543 g/m<sup>2</sup>)

### Tufts\*

104/in<sup>2</sup> (1,611/100 cm<sup>2</sup>)

### Finished Pile Height

0.07" (1.78 mm)

### Average Density (Finished)

7,960

### Standard Backing

PVC-Free Comfort Plus® ES Cushion

Available with TractionBack®

### Recycled Content by Total Weight

ES Backing: 39.6% Pre-Consumer, 0.0% Post-Consumer  
ESP Backing: 29.8% Pre-Consumer, 10.0% Post-Consumer

### Nominal Total Thickness

0.32" (8.1 mm)

### Nominal Total Weight

107 oz/yd<sup>2</sup> (3,628 g/m<sup>2</sup>)

### Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

### Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

### Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 40 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV

### Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

### Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

### Indoor Air Quality—CRI Green Label Plus™

GLP0793, Carpet Category 5Y

### Recommended Installation Method(s)

Ashlar

\* This product utilizes Milliken's patented, high density tufting process called multiple yarn infusion. Conventional measurements of gauge and stitch rate are inadequate and misleading. Therefore, tufts per square inch are shown to provide accurate specifications.

### WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®)

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.